
Subject: Re: Dalitz Decays of higher resonances.
Posted by [Ingo Fröhlich](#) on Thu, 13 Oct 2011 15:36:13 GMT
[View Forum Message](#) <> [Reply to Message](#)

You are absolutely right, there was no flat electron generator enabled. The reason is that the new decays were not recognized as Dalitz-Decays (hardcoded in PData.h).

I did the following changes in PData.h (IsDalitz):

```
int d = makeStaticData()->GetParticleBaryon(id) && // Delta0 Dalitz decay?
((makeStaticData()->IsParticle(i1,"dilepton") &&
 makeStaticData()->GetParticleBaryon(i2)) ||
 (makeStaticData()->GetParticleBaryon(i1) &&
 makeStaticData()->IsParticle(i2,"dilepton")));

return (pseudo&&eeg) || (pseudo&&mumug) ||
(vector&&eepi) || (vector&&mumupi)
|| D0 || Dp || pn || NS0 || NSp || d;
```

now it should print:

Info in <PDalitzModPlugin::ExecCommand>: Model <NS11+_dalitz> uses dGamma/dM for the branching ratio

Info in <PDalitzModPlugin::ExecCommand>: Model <NP110_dalitz> uses dGamma/dM for the branching ratio

Info in <PDalitzModPlugin::ExecCommand>: Model <ND130_dalitz> uses dGamma/dM for the branching ratio

Info in <PDalitzModPlugin::ExecCommand>: Model <NS110_dalitz> uses dGamma/dM for the branching ratio

and:

[ND13+_generator_p_dilepton] Dilepton generator {/generator}
