

---

Subject: [OK] Tracking parametrization

Posted by [Klaus Götzen](#) on Wed, 09 Apr 2014 08:37:53 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Hi,

I put now the sophisticated parametrization to the FsmSimpleTracker class with (reference to Susannas talk)

- dphi(p) according to p. 10
- dtheta(p) -> p. 9
- dp/p(p) -> p. 6
- for  $p < 0.6$ : eff(p) -> p. 8.

They can be switched on by putting negative parameter values for pRes, thRes, phiRes (the values given are then simply ignored if  $< 0$ ) and efficiency, where the efficiency is multiplied with a function shaped like that from p.8, scaling the eff value for  $0 < p < 0.6$  with a factor between 0.55 and 1.0.

However, from a quick check concerning the channels we discussed on Monday I observed, that a flat tracking efficiency of 85% already looks pretty good for 2pi, 4pi, and J/psi pi+ pi- channel. The eta\_c -> phi phi channel is still inconsistent for both the sophisticated and the flat approach, where the flat values even look a bit more similar to full sim results, which is also true for the J/psi. In the figure, the red plots are from flat values, blue are from parametrization. In the J/psi plot, magenta corresponds to full sim. There the flat fast and full sim plots are basically identical with eff\_trk = 85%.

So, our proposal is to keep the flat values as default.

Best,  
Klaus

---

File Attachments

1) [flat\\_vs\\_para.gif](#), downloaded 1284 times

