
Subject: rho-tuple structure

Posted by [Elisabetta Prencipe \(2\)](#) on Fri, 20 Feb 2015 09:44:00 GMT

[View Forum Message](#) <> [Reply to Message](#)

Dear rho-experts,

I am trying to optimize my analysis macro, in rel oct14. The basic analysis tool that I use is /rho/.

In
/PndTools/AnalysisTools/PndRhoTupleQA

I see that several blocks are already prepared with useful variables, and actually I make use and I checked some of those. For example:

```
qa.qaP4("beam", ini, ntp2);  
  
qa.qaComp("Dsm", DslistM[j], ntp2);  
  
qa.qaDalitz("Dsm", DslistM[j], ntp2);  
  
qa.qaVtx("Dsm", DslistM[j], ntp2);
```

work properly.

I would like to use also the block: qa.qaRecoFull("Dsm", DslistM[j], ntp2);

Is it correct to initialize it in such a way? Actually the macro runs, but I do not see the variables which I expect to see in my ntuple, once I write this latter line in my macro. Can anybody of you give help? for example, if I wish to see the distribution of de/dX , or if I wish to have the chi2 and probChi2 distributions inside my ntuple structure (I called it 'ntp2'), what shall I do?

Thank you for your useful help,

Elisabetta
