
Subject: Re: track finder

Posted by [Lia Lavezzi](#) on Fri, 08 Feb 2008 10:37:38 GMT

[View Forum Message](#) <> [Reply to Message](#)

Hi Alicia,

after the Kalman fit you have the track in the SD frame representation, so the 5 parameters are: q/p , v' , w' , v and w . You can access them with the functions in `CbmTrackParP` and `CbmTrackPar` (from which it inherits): `GetQp()`, `GetV()`, and so on. You can also access the x , y , z coordinates and the p_x , p_y , p_z momentum components in the master reference system (you find the functions in the same classes).

Since you talk about the dip angle, and maybe you need it, I explain you how to get it: you need to change your representation, from the SD system (`CbmTrackParP`) to the SC one (`CbmTrackParH`), where the accessible parameters are q/p , λ , ϕ , y_{perp} , z_{perp} . To do this you should use the transformation functions in `CbmGeaneUtil`. Consider as an example in the `kalstt` tutorial, in `kalstt/GeaneEx/CbmGeaneTrKalStt.cxx`, the lines from 298 to 327: they actually perform the reverse transformation, from SD to SC.

One more remark: the Kalman filter procedure does not divide the fit problem into two planes (x - y and z -track length), it is performed on a virtual detector plane; the separation of the problem in the two planes is used only during the prefit (that we perform with an helix in `PndSttHelixTrackFitter`).

Hope this helps, but if you need more info please ask

Ciao,
Lia.