
Subject: Less operator added for pointers in std::map and std::set

Posted by [Bertram Kopf](#) on Tue, 24 Nov 2009 14:14:08 GMT

[View Forum Message](#) <> [Reply to Message](#)

Dear all,

as decided during the last EMC subgroup meeting, I added the less operator for pointers using in std::map's and std::set's. To get the complete PandaRoot code compiling again, one has to modify the packages "lhetrack", "PndTools" and "pid". Due to the fact that I haven't got write permissions for these directories I would kindly like to ask the relevant package coordinators to commit the mandatory changes. What exactly you have to change, you can find in the output of my local svn diff's below:

"svn diff lhetrack"

Toggle Spoiler

Index: lhetrack/PndLhePidMaker.cxx

```
=====
--- lhetrack/PndLhePidMaker.cxx (revision 7036)
+++ lhetrack/PndLhePidMaker.cxx (working copy)
@@ -8,6 +8,7 @@
#include "PndEmcBump.h"
#include "PndEmcDigi.h"
#include "PndEmcStructure.h"
+#include "PndEmcDataTypes.h"
#include "PndEmcXtal.h"
#include "PndMvdHit.h"
#include "PndSttHit.h"
@@ -541,7 +542,7 @@
    vertex.SetXYZ(-10000, -10000, -10000);
}

-    std::map<PndEmcTwoCoordIndex*, PndEmcXtal*>
tciXtalMap=PndEmcStructure::Instance()->GetTciXtalMap();
+    PndEmcTciXtalMap tciXtalMap=PndEmcStructure::Instance()->GetTciXtalMap();
    PndEmcDigi *IDigi= (PndEmcDigi*)emcHit->Maxima();
    PndEmcXtal* xtal = tciXtalMap[IDigi->GetTCI()];
    emcPos = xtal->frontCentre();
```

Index: lhetrack/CMakeLists.txt

```
=====
--- lhetrack/CMakeLists.txt (revision 7036)
+++ lhetrack/CMakeLists.txt (working copy)
@@ -5,7 +5,8 @@
${GEANT3_INCLUDE_DIR}
${CMAKE_SOURCE_DIR}/geobase
${CMAKE_SOURCE_DIR}/parbase
-${CMAKE_SOURCE_DIR}/base
+${CMAKE_SOURCE_DIR}/base
+${CMAKE_SOURCE_DIR}/pndbase/PndStdUtils
${CMAKE_SOURCE_DIR}/field
${CMAKE_SOURCE_DIR}/trackbase
${CMAKE_SOURCE_DIR}/passive
```

"svn diff PndTools"

Toggle Spoiler

Index: PndTools/AnalysisTools/CMakeLists.txt

```
=====  
--- PndTools/AnalysisTools/CMakeLists.txt    (revision 7036)  
+++ PndTools/AnalysisTools/CMakeLists.txt    (working copy)  
@@ -4,7 +4,8 @@  
 ${ROOT_INCLUDE_DIR}  
 ${CMAKE_SOURCE_DIR}/geobase  
 ${CMAKE_SOURCE_DIR}/parbase  
-${CMAKE_SOURCE_DIR}/base  
+${CMAKE_SOURCE_DIR}/base  
+${CMAKE_SOURCE_DIR}/pndbase/PndStdUtils  
 ${CMAKE_SOURCE_DIR}/field  
 ${CMAKE_SOURCE_DIR}/trackbase  
 ${CMAKE_SOURCE_DIR}/pnddata
```

"svn diff pid"

Toggle Spoiler

Index: pid/CMakeLists.txt

```
=====  
--- pid/CMakeLists.txt (revision 7036)  
+++ pid/CMakeLists.txt (working copy)  
@@ -5,7 +5,8 @@  
 ${GEANT3_INCLUDE_DIR}  
 ${CMAKE_SOURCE_DIR}/geobase  
 ${CMAKE_SOURCE_DIR}/parbase  
-${CMAKE_SOURCE_DIR}/base  
+${CMAKE_SOURCE_DIR}/base  
+${CMAKE_SOURCE_DIR}/pndbase/PndStdUtils  
 ${CMAKE_SOURCE_DIR}/field  
 ${CMAKE_SOURCE_DIR}/trackbase  
 ${CMAKE_SOURCE_DIR}/passive
```

Thanks in advance,
Bertram.
