Subject: GEANE: Propagate to Plane not implemented Posted by Tobias Stockmanns on Wed, 15 Oct 2008 06:08:50 GMT View Forum Message <> Reply to Message

Dear GEANE-Developers,

unfortunately the PropagateToPlane function is not implemented in GeanePro. I want to propagate particle tracks onto the surface of my MVD sensors. Which function can I use for it if PropagateToVolume is not working for the MVD and PropagateToPlane is not implemented?

Thank you for your help

**Tobias** 

Subject: Re: GEANE: Propagate to Plane not implemented Posted by Mohammad Al-Turany on Wed, 15 Oct 2008 07:11:35 GMT View Forum Message <> Reply to Message

Hallo Tobias,

## PropagateToVolume:

I am not sure if this will help, but if you use Voulmeld and zero for the copy number then it will propagate to the first node he find with this id! any way we have to investigate if we could give the full name to Geane!

## 2. PropagateToPlane

It is implemented, but not fully! if you choose PropagateToPlane then you have to use :

CbmGeanePro::Propagate(CbmTrackParP \*TStart, CbmTrackParP \*TEnd, Int\_t PDG)

and not the Helix presentation! also this should be trivial to extend, but for now you have the tools to change the representation yourself!

I hope this will help you.

Mohammad

Subject: Re: GEANE: Propagate to Plane not implemented Posted by Tobias Stockmanns on Wed, 15 Oct 2008 07:48:04 GMT View Forum Message <> Reply to Message

Hi Mohammad,

thank you for your reply.

I think I solved the PropagateToPlane problem. There was an error in

CbmGeanePro::PropagateToPlane.

The position of the final plane was not given correctly. The o-Vector was internally calculated as the cross product of u and v, which is wrong. The o-Vector has to come from the plane itself. With this fix at least the propagated points at the plane look reasonably. I still have to figure out if this is true for the errors as well.

Cheers,

**Tobias** 

Subject: Re: GEANE: Propagate to Plane not implemented Posted by Lia Lavezzi on Wed, 15 Oct 2008 08:42:27 GMT

View Forum Message <> Reply to Message

Hi Tobias,

I think the cross product is correct, since in the PropagateToPlane(TVector3 &v0, TVector3 &v1, TVector3 &v2) you give as input the three vectors o, u and v.

They will be given to the EUFILP routine, which says to GEANE to "propagate to plane" in the Propagate(CbmTrackParP \*TStart, CbmTrackParP \*TEnd, Int\_t PDG) function (as Mohammad said).

To do this a vector is filled Float t plo[12], in this way:

```
TVector3 v1u=v1.Unit();
TVector3 v2u=v2.Unit();
// first vector on plane
plo[0]=v1u.X();
plo[1]=v1u.Y();
plo[2]=v1u.Z();
// second vector on plane
plo[3]=v2u.X();
plo[4]=v2u.Y();
plo[5]=v2u.Z();
// origin of the plane
plo[6]=v0.X();
plo[7]=v0.Y();
plo[8]=v0.Z();
// normal to the plane (the third vector to define the reference system u, v, w)
TVector3 v3=v1u.Cross(v2u);
plo[9]=v3(0);
plo[10]=v3(1);
plo[11]=v3(2);
```

So what did you exactly change?

Subject: Re: GEANE: Propagate to Plane not implemented Posted by Tobias Stockmanns on Wed, 15 Oct 2008 09:29:02 GMT View Forum Message <> Reply to Message

Hi Lia,

you are right. I modified the lines with plo[9] = v0.), plo[10] = v0.Y(), plo[11].v0.Z().

Which is wrong but did not cause any harm, because v0 is orthogonal to v1 and v2.

I corrected it in my code and switched to CbmTrackParP. Now the code runs stable but the results are a puzzling.

I have simulated a 1 GeV proton flying through the MVD. I take Geane to predict the point on the various detector planes from the first point in the MVD. For most of the points the prediction works in the way that the predicted points are close to the MC points from the simulation but some of the points are far outside the detector.

In addition the given errors from Geane are for the x and y coordinate of the points too low and not consistent. For the z coordinate it seems to fit. At least the pull distribution looks reasonable. I have added the two pull distributions to this message. The diagrams are restricted to a range of -10 to 10 otherwise you could not see anything because some pulls get really big.

I hope you have an idea, why this happens.

Cheers

**Tobias** 

## File Attachments

- 1) PullDistributionX.pdf, downloaded 381 times
- 2) PullDistributionZ.pdf, downloaded 388 times

Subject: Re: GEANE: Propagate to Plane not implemented Posted by Lia Lavezzi on Wed, 15 Oct 2008 10:05:52 GMT

View Forum Message <> Reply to Message

#### Quote:

I modified the lines with plo[9] = v0.Dead), plo[10] = v0.Y(), plo[11].v0.Z(). Which is wrong but did not cause any harm, because v0 is orthogonal to v1 and v2.

...ok, just pay attention that you need the triplet v0, v1, v2 to be right handed...

Concerning the results you get, if you plot GeaneTrackPar.fX - GeaneTrackFinal.fX is it

correct? I mean, is it centered at 0? Is there a problem only on the error calculation or also on the parameter value?

It's not easy to understand what happens without looking at to code ... is your code in the svn repository? Can I have a look at (and maybe try to run) it, please?

Ciao, Lia.

Subject: Re: GEANE: Propagate to Plane not implemented Posted by Lia Lavezzi on Wed, 15 Oct 2008 10:26:26 GMT View Forum Message <> Reply to Message

Hi again,

one more remark: Susanna suggested also that to plot the pull distributions and correctly compare the MC to the GEANE output you need to change some cuts following the instructions in gconfig/SetCuts.C and rerun both the simulation and GEANE.

We are afraid this will not completely solve the problem, but maybe it will improve a little the results.

Lia.

Subject: Re: GEANE: Propagate to Plane not implemented Posted by Tobias Stockmanns on Wed, 15 Oct 2008 11:01:08 GMT View Forum Message <> Reply to Message

Hi Lia,

here is the class I am using to run GEANE and the corresponding macro.

You have to copy the class into the pandaroot/mvd/MvdTools folder and modify the CMakeLists.txt and MvdLinkDef.h files.

For the macro you have to run first the runMvdSim.C macro. Be sure that the output file of runMvdSim.C matches the input file of runGeane.C.

Thank you very much for your help.

Cheers,

**Tobias** 

## File Attachments

- 1) PndMvdMSAnaTask.cxx, downloaded 378 times
- 2) PndMvdMSAnaTask.h, downloaded 372 times
- 3) runGeane.C, downloaded 395 times

# Subject: Re: GEANE: Propagate to Plane not implemented Posted by Lia Lavezzi on Wed, 15 Oct 2008 17:00:29 GMT

View Forum Message <> Reply to Message

Hi Tobias,

I had a look at the code and here is what I found:

- 1) in the task the fPro->PropagateFromPlane(startU, startV) is missing;
- 2) GEANE does not see any magnetic field since in the simulation macro runSimMvd.C the lines to save the magnetic field to the parameter file are missing.

After getting the RuntimeDataBase:

```
CbmRuntimeDb *rtdb=fRun->GetRuntimeDb();
Bool_t kParameterMerged=kTRUE;
CbmParRootFileIo* output=new CbmParRootFileIo(kParameterMerged);
output->open(parOutput.Data(),"RECREATE");
rtdb->setOutput(output);
```

These lines should be added:

```
PndMultiFieldPar* fieldPar = (PndMultiFieldPar*) rtdb->getContainer("PndMultiFieldPar"); if (fField) { fieldPar->SetParameters(fField); } fieldPar->setInputVersion(fRun->GetRunId(),1); fieldPar->setChanged();
```

In this way GEANE can find the field.

I attach some results I got with this change:

res\_withB and res\_withoutB are the simple GEANE - MonteCarlo x coordinate; pull\_withB and pull\_withoutB are the pull distributions.

Ciao, Lia.

# File Attachments

- 1) res\_withoutB.ps, downloaded 365 times
- 2) res\_withB.ps, downloaded 352 times
- 3) pull\_withoutB.ps, downloaded 351 times
- 4) pull\_withB.ps, downloaded 342 times

Subject: Re: GEANE: Propagate to Plane not implemented Posted by Tobias Stockmanns on Thu, 16 Oct 2008 07:13:14 GMT View Forum Message <> Reply to Message

Hi Lia,

you are great.

Now it looks like I would expect it. There are still a few rare hits outside the detector but the distributions are perfectly fine.

Thank you again for your help.
Ciao,
Tobias
Page 6 of 6 Generated from GSI Forum