

---

Subject: [SOLVED] PAnyDistribution Add Multiple equation  
Posted by [Michael Kunkel](#) on Sat, 29 Sep 2012 05:22:29 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

Greetings

I would like to implement several logic statements into a distribution using PAnyDistrubution.

I tried to model this by mimicking the example macro demo\_PAnyDistribution in the macros directory.

```
TH1F * cache = new TH1F ("cache","Rho0 t cache",400,-4.0,0.0);
```

```
decay->AddEquation(cache,"beam = _parent->GetBeam(); beam->Boost(_parent) ; t1 =  
(beam - [rho0])->Mag2(); _x = t1;");
```

```
decay->AddEquation("beam2 = _parent->GetBeam(); beam2->Boost(_parent); if (beam2 <  
4.6) _f = exp( 6.9*t1 ); if (beam2 > 4.6) _f = exp( 8.9*t1 );");
```

It seems I do not understand, because PLUTO will always execute the first "IF" statement regardless of the beam energy.

If this something I would have to use a 2D histogram for? A 2D histogram seems overkill for a project like this.

Thanks

---

Subject: Re: PAnyDistribution Add Multiple equation  
Posted by [Ingo Froehlich](#) on Sun, 30 Sep 2012 17:09:42 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

This does not work for 2 reasons: you use "beam2", which is an object, so what you practically do is to test on the existence of the particle object, and therefore the first "if" always returns true. And also, the if-statements are excluding each other: if the first condition is true, the second one will always give a negative result, and thus the last part will never be executed.

I'm not sure which observable you want to use (kinetic energy?), therefore I also cannot judge if the boost is really what you want do. I can only provide you the following template:

```
decay->AddEquation("beam2 = _parent->GetBeam(); if (beam2->KE() < 4.6) _f = exp( 6.9*t1  
);");  
decay->AddEquation("if (beam2->KE() >= 4.6) _f = exp( 8.9*t1 );");
```

---

Subject: Re: PAnyDistribution Add Multiple equation

Posted by [Michael Kunkel](#) on Mon, 01 Oct 2012 00:59:12 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

The observable I am attempting to control is the t-slope as a function of beam energy. I assumed `_parent->GetBeam()` would be the beam energy alone and I would have to boost this into to c.m. of the system.

As the way you wrote the example,

```
decay->AddEquation("beam2 = _parent->GetBeam(); if (beam2->KE() < 4.6) _f = exp( 6.9*t1 );");  
decay->AddEquation("if (beam2->KE() >= 4.6) _f = exp( 8.9*t1 );");
```

This beam2 is in the lab frame, I presume?

---