
Subject: Fast Simulation- neutral particle
Posted by [Lu Cao](#) on Mon, 31 Mar 2014 14:24:37 GMT
[View Forum Message](#) <> [Reply to Message](#)

Hi all,

I try to do fast simulation with this decay chain: $p\bar{p} \rightarrow D_s^+ D_s^-$; $D_s^- \rightarrow K^+ K^- \pi^-$; $D_s^+ \rightarrow e^+ \nu_e \eta$; $\eta \rightarrow \pi^+ \pi^- \pi^0$ (gamma gamma). From the examples in macro/scrut, I got some problems for simulating the neutral channel:

1) in simulation macro:

```
// generate electro-magnetic / hadronic split offs in the EMC? switch off when running w/o EMC
```

```
Bool_t enableSplitoff = kFALSE;
```

```
//enable the producing of parametrized neutral (hadronic) split offs  
if (enableSplitoff)
```

```
    fastSim->EnableSplitoffs(BaseDir+"/fsim/splitpars.dat");
```

From the comments there, if I understand correctly, the "enableSplitoff" seems should be switched on for $\eta \rightarrow \pi^+ \pi^- \pi^0$ (gamma gamma). I tried kTRUE, but it crashed.

2) in analysis:

```
// *** name of the only PidAlgo TClonesArray in fsim  
TString pidalg = "PidChargedProbability";
```

Does it mean no neutral algorithm in fast simulation? then, how to fill the neutral list?

Thanks in advance.

Lu

Subject: Re: Fast Simulation- neutral particle
Posted by [Klaus Götzen](#) on Tue, 01 Apr 2014 06:09:44 GMT
[View Forum Message](#) <> [Reply to Message](#)

Dear Lu,

actually you don't need the turn on that split-offs switch for your channel. The generation of e.-m. and hadronic split-offs was supposed to somehow remodel neutral secondaries induced by charged tracks. However the code is quite old and was parametrized in the 'old' Babar-like framework. Therefore it should be taken with care. But at least it shouldn't crash, so I'm gonna take a look.

Best,
Klaus

Subject: Re: Fast Simulation- neutral particle
Posted by [Klaus Götzen](#) on Tue, 01 Apr 2014 07:09:56 GMT
[View Forum Message](#) <> [Reply to Message](#)

Dear Lu,

I just updated macro/scrut concerning the split-off generation. If you like you can svn up that directory and retry with using split-offs to see the difference in the neutrals multiplicity. Please let me know if it still crashes.

Best,
Klaus

Subject: Re: Fast Simulation- neutral particle
Posted by [Lu Cao](#) on Tue, 01 Apr 2014 09:05:17 GMT
[View Forum Message](#) <> [Reply to Message](#)

Dear Klaus,

Thanks. It works now.
Then, coming to the second question, since "PidChargedProbability" is for charged particle, how to fill the neutral list?

Best regards,
Lu

Subject: Re: Fast Simulation- neutral particle
Posted by [Stefano Spataro](#) on Tue, 01 Apr 2014 09:43:42 GMT
[View Forum Message](#) <> [Reply to Message](#)

How do you fill photon list in the full reco? It should be the same.

Subject: Re: Fast Simulation- neutral particle
Posted by [Lu Cao](#) on Tue, 01 Apr 2014 10:46:36 GMT
[View Forum Message](#) <> [Reply to Message](#)

In the full reconstruction, I used
theAnalysis->FillList(gam,"Neutral");
but it makes the ana macro crash in the fast sim with this warning:
Warning in <PndAnaPidCombiner::PndAnaPidCombiner::ReadTCA()>: No
"PidAlgoIdealCharged" array found.
*** Break *** segmentation violation

Best regards,

Lu

Subject: Re: Fast Simulation- neutral particle

Posted by [Klaus Götzen](#) on Tue, 01 Apr 2014 11:24:13 GMT

[View Forum Message](#) <> [Reply to Message](#)

Yes, just take the same name 'PidChargedProbability' for neutrals, I think without that parameter the FillList crashes (Ralf is looking at it...).

Best,
Klaus

Subject: Re: Fast Simulation- neutral particle

Posted by [Elisabetta Prencipe \(2\)](#) on Wed, 02 Apr 2014 13:40:11 GMT

[View Forum Message](#) <> [Reply to Message](#)

Dear Klaus and Ralf,

it is still not clear to me how we should fill up the neutral list in the new release.
I am running in the trunk 24275 right now.

For example, in the old release if I type:

```
theAnalysis->FillList(gammas, "Neutral");
```

this works ["works"....great word! At least it does not produce a crash]

In the new /macro/scrut for charged particles one has to fill up lists in this way:

```
theAnalysis->FillList(kplus, "KaonAllPlus", pidalg); //example for kaon+ list
```

But for neutral particles I think it is wrong to write:

```
theAnalysis->FillList(gammas, "Neutral", pidalg);
```

especially if I read in the macro:

```
// *** name of the only PidAlgo TClonesArray in fsim  
TString pidalg = "PidChargedProbability";
```

Now, to write simply:

```
theAnalysis->FillList(gammas, "Neutral");
```

gives a Seg Fault, as the info concerning the pid-algorithm MUST be passed, for how this is defined.

So, my question follows that posed from Lu in the past days: how shall we fill up the list of neutrals in the new release? Without this, here we are stacked, as in all channels we try to reconstruct, at least one photon gets involved.

Thank you for your suggestion,

Elisabetta

Subject: Re: Fast Simulation- neutral particle
Posted by [Ralf Kliemt](#) on Wed, 02 Apr 2014 13:51:02 GMT
[View Forum Message](#) <> [Reply to Message](#)

Hi,

I'm on it. You should never have been forced to provide a PidAlgo.

Cheers
Ralf

Subject: Re: Fast Simulation- neutral particle
Posted by [Elisabetta Prencipe \(2\)](#) on Wed, 02 Apr 2014 13:59:25 GMT
[View Forum Message](#) <> [Reply to Message](#)

Hi Ralf,

thank you to take care of this. If I do not write any pid information in the neutral list, I got a Segmentation Fault. So I cannot run that macro at all.

If I define a new string:

```
TString pidalg0 = "PidNeutralProbability";
```

and I pass this parameter, actually it runs. Would it be ok, in your opinion?

I see that in PidClassifier/PndPidIdealAssociatorTask.cxx, "PidNeutralProbability"; exists.

cheers, Elisabetta

Subject: Re: Fast Simulation- neutral particle
Posted by [Ralf Kliemt](#) on Wed, 02 Apr 2014 14:18:38 GMT
[View Forum Message](#) <> [Reply to Message](#)

Hi Elisabetta,

Yes, it would be OK as long as you don't access PID information. I.e. don't select on the

numbers from the charged PID in your neutral candidates.

Cheers
Ralf

Subject: Re: Fast Simulation- neutral particle
Posted by [Lu Cao](#) on Wed, 02 Apr 2014 14:20:31 GMT
[View Forum Message](#) <> [Reply to Message](#)

Hi Ralf,

Regarding to the issue of FillList, I just found that scrut/ana_jpsi.C crashes due to this operation:

```
theAnalysis->FillList(mclist, "McTruth");
```

It doesn't work any more in the version of 24297, but works with the previous one #24275 (Elisabetta tests).

Is it caused by the on-going modifications of code? and can be fixed in soon?

Thanks in advance.

Best,
Lu

Subject: Re: Fast Simulation- neutral particle
Posted by [Ralf Kliemt](#) on Wed, 02 Apr 2014 14:37:35 GMT
[View Forum Message](#) <> [Reply to Message](#)

Hi.

I checked in the fix for not providing a pidalgo.

Regarding the issue with FillList(... "MCTruth") I found nothing wrong in my fresh trunk. Please see with svn diff if you have some accidental changes.

Cheers
Ralf

Subject: Re: Fast Simulation- neutral particle
Posted by [Lu Cao](#) on Wed, 02 Apr 2014 15:33:13 GMT
[View Forum Message](#) <> [Reply to Message](#)

Hi,
I didn't touch the example code...and it still doesn't work even for the newly download.
uh...what can I do anyway?

Best,
Lu

Subject: Re: Fast Simulation- neutral particle
Posted by [Klaus Götzen](#) on Wed, 02 Apr 2014 15:43:23 GMT
[View Forum Message](#) <> [Reply to Message](#)

Hi Lu,

I just checked out mar14 and run the example with

```
root -l -b -q 'simfast.C("psi","psi2s_jpsi2mu_2pi.dec",6.23,1000,"psi(2S)")'  
root -l -b 'ana_jpsi.C("psi_fast.root")'
```

and it runs without any problem.

Did you start a new shell for checking out and compiling and stuff? It can always be that your environment is spoiled, which leads to strange effects.

Best,
Klaus

Subject: Re: Fast Simulation- neutral particle
Posted by [Lu Cao](#) on Wed, 02 Apr 2014 16:09:35 GMT
[View Forum Message](#) <> [Reply to Message](#)

Hi Klaus,

Thanks for your checking. My problem sounds pretty strange somehow.. The working environment looks fine, and ana_jpsi.C can work when I comment the line filling the MC list. By the way, I met a problem in compiling mar14:

[93%] Built target LmdTool

[93%] Building CXX object

```
lmd/CMakeFiles/Model.dir/LmdFit/ModelFramework/fit/ModelFitFacade.cxx.o  
/private/pandaroot_mar14/pandaroot/lmd/LmdFit/ModelFramework/fit/ModelFitFacade.cxx: In  
member function 'ModelFitResult ModelFitFacade::Fit()':  
/private/pandaroot_mar14/pandaroot/lmd/LmdFit/ModelFramework/fit/ModelFitFacade.cxx:68:1  
1: error: no match for 'operator==' in '0 ==  
((ModelFitFacade*)this)->ModelFitFacade::estimator'  
/private/pandaroot_mar14/pandaroot/lmd/LmdFit/ModelFramework/fit/ModelFitFacade.cxx:68:1  
1: note: candidate is: operator==(int, int) <built-in>  
/private/pandaroot_mar14/pandaroot/lmd/LmdFit/ModelFramework/fit/ModelFitFacade.cxx:81:1  
1: error: no match for 'operator==' in '0 ==  
((ModelFitFacade*)this)->ModelFitFacade::minimizer'  
/private/pandaroot_mar14/pandaroot/lmd/LmdFit/ModelFramework/fit/ModelFitFacade.cxx:81:1
```

```
1: note: candidate is: operator==(int, int) <built-in>
make[2]: *** [Imd/CMakeFiles/Model.dir/LmdFit/ModelFramework/fit/ModelFitFacade.cxx.o]
Error 1
make[1]: *** [Imd/CMakeFiles/Model.dir/all] Error 2
make: *** [all] Error 2
```

Best,
Lu

Subject: Re: Fast Simulation- neutral particle
Posted by [Klaus Götzen](#) on Wed, 02 Apr 2014 16:17:51 GMT
[View Forum Message](#) <> [Reply to Message](#)

Hi Lu,

do you work on your own computer? Maybe it's something with the external packages?
Because it just worked for me half an hour ago on my GSI machine.

Best,
Klaus

Subject: Re: Fast Simulation- neutral particle
Posted by [Lu Cao](#) on Wed, 02 Apr 2014 16:22:15 GMT
[View Forum Message](#) <> [Reply to Message](#)

Hi Klaus,

I'm using own computer with the external package of apr13. There's no problem before today...

Best,
Lu

Subject: Re: Fast Simulation- neutral particle
Posted by [Stefan Pflueger](#) on Thu, 03 Apr 2014 09:10:32 GMT
[View Forum Message](#) <> [Reply to Message](#)

Hello Lu,

I uploaded a fix for this compilation error. Could you give it a test and let me know if it works?
Thank you.

Cheers,
Stefan

Subject: Re: Fast Simulation- neutral particle
Posted by [Lu Cao](#) on Thu, 03 Apr 2014 12:06:17 GMT
[View Forum Message](#) <> [Reply to Message](#)

Hi Stefan,

it still has the same error during installing.

Best,
Lu

Subject: Re: Fast Simulation- neutral particle
Posted by [Stefan Pflueger](#) on Thu, 03 Apr 2014 13:01:02 GMT
[View Forum Message](#) <> [Reply to Message](#)

Hi,

@Lu:

ah sry, I just saw that you are using the mar14 release... That would explain the same error. I committed this fix into the trunk. I actually do not know if I'm allowed to commit to the release code.

@all:

How am I supposed to commit this change into the release branch? I tried to switch this file to the mar14 version, apply the fix and then commit this file. However the permission for the commit was denied. Is this the wrong way to fix it or am I simply missing the permissions.

Best regards,

Stefan

Subject: Re: Fast Simulation- neutral particle
Posted by [Stefano Spataro](#) on Thu, 03 Apr 2014 13:10:39 GMT
[View Forum Message](#) <> [Reply to Message](#)

I will do this, just give me the time to reach a PC.

Subject: Re: Fast Simulation- neutral particle
Posted by [Stefano Spataro](#) on Thu, 03 Apr 2014 13:45:58 GMT
[View Forum Message](#) <> [Reply to Message](#)

Now mar14 is updated, please try now.

Subject: Re: Fast Simulation- neutral particle

Posted by [Lu Cao](#) on Thu, 03 Apr 2014 14:11:56 GMT
[View Forum Message](#) <> [Reply to Message](#)

The installation works now, and the example in scrut also works.

Thanks to all helps.

Lu
