Subject: [FIXED] Produce ROOT file with FairRoot Structure Posted by wesmail on Mon, 19 Mar 2018 12:24:35 GMT View Forum Message <> Reply to Message

Dear experts,

I have a ROOT file that contains probability distributions of different particles (e, mu, pi, k, p) stored in TClonesArray "branch named PidAlgoMI" (image 1), but I want it to be of the same structure of image 2, that is the branch "PidAlgoMI" inside folder "Pid" which is inside folder "cbmout". How to do this using PANDARoot or FairROOT classes.

Thank you very much in advance,

File Attachments
1) 1.png, downloaded 937 times

Page 1 of 6 ---- Generated from GSI Forum

Esmail, Waleed Ahmed - Outl	🥑 matching.C - /home/wesmail	ROOT Object Browser
-----------------------------	------------------------------	---------------------

🔳 Terminal - we

<u>File Edit View T</u>erminal T<u>a</u>bs <u>H</u>elp

6

wesmail@wesmail-X580VD: ~/findspark-1.1.0



2) 2.png, downloaded 803 times

Page 3 of 6 ---- Generated from GSI Forum

놀 Esmail, Waleed Ahmed - Outl... 🛞 matching.C - /home/wesmail... 阳 ROOT Object Browser

ആ

🔳 Terminal - we

Filter: All Files (*.*)



Subject: Re: Produce ROOT file with FairRoot Structure Posted by StefanoSpataro on Mon, 19 Mar 2018 12:42:33 GMT View Forum Message <> Reply to Message

How have you created your container? The proper way is using a Task which fills for each event and each PidCandidate the proper probabilities.

The correct way is shown, as example, in pid/PidClassifier/PndPidDrcAssociatorTask class, which is quite simple. You have to follow such structure, just change the name of the classes and the numbers you put inside.

cbmout.pid.XXX is not business of the developer if you use the suggested structure. Anyway, the line which write your container inside pid is:

FairRootManager::Instance()->Register("PidAlgoDrc","Pid", fPidChargedProb, kTRUE);

Subject: Re: Produce ROOT file with FairRoot Structure Posted by wesmail on Mon, 19 Mar 2018 13:20:46 GMT View Forum Message <> Reply to Message

Dear Stefano,

thank you very much for your instant reply. I am aware of the associator task, but I don't know how to use it because at Init() method it tries to get the TClonesArray from the input file and I face the same problem ("PidAlgoMI is not in cbmout folder" because my file is not in the same RootFair structure) and crashes.

N.B I fill the TClonesArray in a python program independent of FairRoot package, but I can access FairRoot from python. How to use Register method independent from associator Task?!.

Thank you again,

Subject: Re: Produce ROOT file with FairRoot Structure Posted by StefanoSpataro on Mon, 19 Mar 2018 13:26:27 GMT View Forum Message <> Reply to Message

The starting point is a TClonesArray filled with PidCandidate objects, event by event. For each event, for each PidCandidate, the Associator produces a PidProbability object, and registers it. Without the input PidCandidate you cannot fill the probabilities. Other ways to fill TCAs, such us using python, are not using the fairroot tree and are not

compatible. Register is a function of fairroot, then you cannot use it in python.

Subject: Re: Produce ROOT file with FairRoot Structure Posted by Waleed Esmail on Wed, 21 Mar 2018 09:13:38 GMT View Forum Message <> Reply to Message thank you very much, I solved the problem by reading the output python file explicitly in the Init() method of the associator task, and register the output to have the same branch structure of FairRoot.

Thanks again for your help

```
Page 6 of 6 ---- Generated from GSI Forum
```