Subject: Changes in simplified digitisation of emc Posted by Dima Melnychuk on Fri, 18 Dec 2009 13:13:48 GMT View Forum Message <> Reply to Message

Hi all,

I have modified a little bit simplified digitisation of emc to take into account two most relevant parameters: electronic noise and photon statistics.

With UseDigiEffectiveSmearing=1 parameter in emc.par the task PndEmcMakeDigi will smear energy taking into account parameters DetectedPhotonsPerMeV, ExcessNoiseFactor and Incoherent_elec_noise_width_GeV according to:

sigma/E=sqrt((a/sqrt(E))^2+(E_noise/E)),

where a=sqrt(F/N_p.e.),

F - excess noise factor and N_p.e. - number of photoelectrons.

This option can be useful for comparison with prototype data.

Best regards, Dima

Subject: Re: Changes in simplified digitisation of emc Posted by Johan Messchendorp on Tue, 12 Jan 2010 21:24:53 GMT View Forum Message <> Reply to Message

Hi Dima,

Thanks for the update; a simplification algorithm is always good! To let you know, I incremented the version number of the PndEmcDigiPar class by one. This because it caused in some cases troubles in reading the parameter database files in the case older versions were not deleted. In those cases it was not recognised by the framework that an uncompatible set of parameters was present in the database file. The bottom line, we should not forget to update the class version number as well....

Greetings,

Johan.