

---

Subject: A bug in FairRootManager

Posted by [Jifeng Hu](#) on Tue, 14 Jan 2014 15:03:32 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

The Data Exchange between tasks is supported by FairRootManager. In normal, different TClonesArray in many tasks are created and registered in FairRootManager, then also could be retrieved. FairRootManager provides many interfaces to do that.

For example, create and register a TClonesArray in a way

(A)

```
fEmcDigiArray = new TClonesArray("PndEmcDigi");// PndEmcDigi, Class Name
FairRootManager::Instance()->Register("EmcDigi", "Emc", fEmcDigiArray, kTRUE);
where "PndEmcDigi" is the Class Name, "EmcDigi" is the Branch Name, "Emc" is the Folder Name.
```

or another way,

(B)

```
fEmcDigiArray = FairRootManager::Instance()->Register("EmcDigi", "PndEmcDigi", "Emc",
kTRUE);
```

However, when we want to retrieve this branch,

```
fEmcDigiArrayRef = FairRootManager::Instance()->GetTClonesArray("EmcDigi");
```

retrieval fails when in way of (A), and succeeds in way of (B).

The reason for that is a bug inside FairRootManager.

When invoking (B), an active container (std::map) was filled, and skipped when invoking (A).

So please either uniform a standard interface or make a new logic.

---

---

Subject: Re: A bug in FairRootManager

Posted by [Stefano Spataro](#) on Tue, 14 Jan 2014 16:56:00 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Dear Jifeng,

since this topic is about base classes and not pandaroot, it would be better to post it under fairroot topic here. At least they can check and modify the code, we cannot.

---